



Key Features

- 1780 Lumens
- High CRI (82+)
- 10,000 hour average life
- Even light distribution

Other information

- Operating temperature range between -20°C and +40°C
- UL/cUL listed, FCC compliant
- 1-year limited warranty in commercial and residential use

Applications

- Commercial
- Residential
- Hospitality
- Restaurants
- Property Management

General Usage

- General lighting
- Recessed Down Lights/Pot Lights
- Specialty

Order Code	Model Number	Watts	Base	Hour Rating	Initial Lumens	CCT (K)	CRI	M.O.L. (inch)	Case Qty.
1162105	TUFF-PLC-13W/27/4P	13	G24q-1	10,000	890	2700	82	5.63	25
1162302	TUFF-PLC-13W/35/4P	13	G24q-1	10,000	890	3500	82	5.63	25
1162405	TUFF-PLC-13W/41/4P	13	G24q-1	10,000	860	4100	82	5.63	25
1162502	TUFF-PLC-13W/50/4P	13	G24q-1	10,000	840	5000	82	5.63	25
1163100	TUFF-PLC-18W/27/4P	18	G24q-2	10,000	1200	2700	82	6.42	25
1163300	TUFF-PLC-18W/35/4P	18	G24q-2	10,000	1200	3500	82	6.42	25
1163400	TUFF-PLC-18W/41/4P	18	G24q-2	10,000	1180	4100	82	6.42	25
1163500	TUFF-PLC-18W/50/4P	18	G24q-2	10,000	1120	5000	82	6.42	25
1164100	TUFF-PLC-26W/27/4P	26	G24q-3	10,000	1780	2700	82	7.21	25
1164300	TUFF-PLC-26W/35/4P	26	G24q-3	10,000	1780	3500	82	7.21	25
1164400	TUFF-PLC-26W/41/4P	26	G24q-3	10,000	1730	4100	82	7.21	25
1164500	TUFF-PLC-26W/50/4P	26	G24q-3	10,000	1680	5000	82	7.21	25

How to read: TUFF - PLC - 13W / 27 / 4P

Series Lamp Type Wattage CCT(K) Pin Type

Distributed by:

