



Turolight's T8 fluorescent lamps will meet and surpass your project requirements while saving your money in both energy consumption and product cost without sacrificing quality or efficiency!



**TUFF™**

## “WHAT YOU “CEE” IS WHAT YOU GET!

Our 25W, 28W and 32W T8's sub ranges meet CEE(Consortium for Energy Efficiency) for only the highest performance making them suitable for government incentive programs!

### Key Features

- **3100 Lumens**
- **Meets CEE for Lumen Efficacy**
- **94% Lumen maintenance**
- **Improved black-end cathode protection\***
- **Also available in 25W/4Ft and 28W/4Ft**
- **High CRI (85+)**
- **30,000 hour average life**
- **Reduces energy consumption up to 20%**
- **Shatterproof available**

\*Controlled and programmed start greatly reduces the amount and rate of lamp end-blackening "coil sputter" that occurs to the lamp during normal operation.

### Applications

- Office buildings
- Industrial units
- Warehouses
- Shopping malls
- Garages
- Cabinets
- Residential
- Condominiums
- Schools
- Hospitals
- Hotels
- Supermarkets

### Other information

- Operating temperature range between -20°C and +40°C
- UL/cUL listed, FCC compliant
- Available in these color temperatures: 3000K, 3500K, 4100K, 5000K, and 6500K\*\*
- 2-year limited warranty in commercial and residential use

\*\*6500K available for selected items.

### General Usage

- Ceiling Fixtures
- Track Lights
- Specialty
- Ideal replacement of T8 & T12 fixtures

Order Code	Model Number	CEE	Watts	Base	Hour Rating <sup>†</sup>		Initial Lumens	Mean Lumens	CCT (K)	CRI	M.O.L. (inch)	Qty.
					(3 hour start)	(12 hour start)						
<b>TUFF™ T8 - Rapid Start</b>												
1363200	TUFF-F17T8/830	-	17	Med Bi Pin / G13	30,000	36,000	1400	1316	3000K	85	24	25
1363300	TUFF-F17T8/835	-	17	Med Bi Pin / G13	30,000	36,000	1400	1316	3500K	85	24	25
1363400	TUFF-F17T8/841	-	17	Med Bi Pin / G13	30,000	36,000	1400	1316	4100K	85	24	25
1363500	TUFF-F17T8/850	-	17	Med Bi Pin / G13	30,000	36,000	1300	1222	5000K	85	24	25
1363600	TUFF-F17T8/865	-	17	Med Bi Pin / G13	30,000	36,000	1300	1222	6500K	85	24	25
1364200	TUFF-F25T8/830	-	25	Med Bi Pin / G13	30,000	36,000	2175	2045	3000K	85	36	25
1364300	TUFF-F25T8/835	-	25	Med Bi Pin / G13	30,000	36,000	2175	2045	3500K	85	36	25
1364400	TUFF-F25T8/841	-	25	Med Bi Pin / G13	30,000	36,000	2175	2045	4100K	85	36	25
1364500	TUFF-F25T8/850	-	25	Med Bi Pin / G13	30,000	36,000	2000	1880	5000K	85	36	25
1364602	TUFF-F25T8/865	-	25	Med Bi Pin / G13	30,000	36,000	2000	1880	6500K	85	36	25
1364201	TUFF-F32T8/830/25W	✓	25	Med Bi Pin / G13	30,000	36,000	2400	2256	3000K	85	48	25
1364301	TUFF-F32T8/835/25W	✓	25	Med Bi Pin / G13	30,000	36,000	2400	2256	3500K	85	48	25
1364401	TUFF-F32T8/841/25W	✓	25	Med Bi Pin / G13	30,000	36,000	2400	2256	4100K	85	48	25
1364501	TUFF-F32T8/850/25W	✓	25	Med Bi Pin / G13	30,000	36,000	2350	2209	5000K	85	48	25
1364603	TUFF-F32T8/865/25W	✓	25	Med Bi Pin / G13	30,000	36,000	2350	2209	6500K	85	48	25
1364202	TUFF-F32T8/830/28W	✓	28	Med Bi Pin / G13	30,000	36,000	2700	2538	3000K	85	48	25
1364302	TUFF-F32T8/835/28W	✓	28	Med Bi Pin / G13	30,000	36,000	2700	2538	3500K	85	48	25
1364402	TUFF-F32T8/841/28W	✓	28	Med Bi Pin / G13	30,000	36,000	2700	2538	4100K	85	48	25
1364502	TUFF-F32T8/850/28W	✓	28	Med Bi Pin / G13	30,000	36,000	2600	2444	5000K	85	48	25
1364604	TUFF-F32T8/865/28W	✓	28	Med Bi Pin / G13	30,000	36,000	2600	2444	6500K	85	48	25
1364203	TUFF-F32T8/830	✓	32	Med Bi Pin / G13	30,000	36,000	3100	2914	3000K	82	48	25
1364303	TUFF-F32T8/835	✓	32	Med Bi Pin / G13	30,000	36,000	3100	2914	3500K	82	48	25
1364403	TUFF-F32T8/841	✓	32	Med Bi Pin / G13	30,000	36,000	3100	2914	4100K	82	48	25
1364503	TUFF-F32T8/850	✓	32	Med Bi Pin / G13	30,000	36,000	3000	2820	5000K	85	48	25
1364601	TUFF-F32T8/865	✓	32	Med Bi Pin / G13	30,000	36,000	3000	2820	6500K	85	48	25
<b>TUFF™ T8 - Rapid Start Shatter-Proof</b>												
1364409	TUFF-F32T8/841/TC	✓	32	Med Bi Pin / G13	30,000	36,000	3100	2914	4100K	82	48	25
1364509	TUFF-F32T8/850/TC	✓	32	Med Bi Pin / G13	30,000	36,000	3000	2820	5000K	82	48	25
<b>TUFF™ T8 - Rapid Start U-Shape</b>												
1364207	TUFF-F32T8/U/830	-	32	Med Bi Pin / G13	24,000	28,000	2730	2600	3000K	82	24	20
1364307	TUFF-F32T8/U/835	-	32	Med Bi Pin / G13	24,000	28,000	2730	2600	3500K	82	24	20
1364407	TUFF-F32T8/U/841	-	32	Med Bi Pin / G13	24,000	28,000	2730	2600	4100K	82	24	20
1364507	TUFF-F32T8/U/850	-	32	Med Bi Pin / G13	24,000	28,000	2625	2500	5000K	82	24	20

## Meet Our T8 Recessed Office & High Bay Fixture

- Sturdy Heavy Duty Design
- Smooth Edges (Reduces Risk of Injury)
- Hinged Door Diffuser
- Slim Profile



CALL FOR MORE DETAILS!

How to read: TUFF - F32T8 / 8 50 / 25W  
 Lamp Class    Type    CRI    CCT(K)    Wattage

Distributed by:



TO ORDER PLEASE CALL 1-877-736-0447 OR EMAIL: SALES@TUROLIGHT.COM

Tel: (416) 736-0447 • Toll Free: 1 (877) 736-0447 • Fax: (416) 736-4890 • Email: info@turolight.com • Website: www.turolight.com