

LED LAMP

VIVID Series



VIV-T8BPSP4, VIV-T8BPSP



Features & Benefits

DLC approved*, Dimmable*	24", 36" and 48" length
Ballast Bypass (no ballast required)	NSF/ANSI 2 Certified ¹
50,000 hour life (L70), 180° Beam angle, High CRI (83+)	Suitable for splash zones of food equipment
Perfect replacement for T8 linear fluorescent	Fits into existing linear fixtures

¹Need to work with NSF certified lighting fixtures

Dimensional drawing



Warranty & Cautions

5-year limited warranty for DLC listed lamps / 3-year limited warranty for non-DLC*

Bulb wall temperature range between -20°C and +45°C

Sockets must be non-shunted

*For applicable models, see product specification below

Product Specification

Ordering Code	DLC	Model Number	Description	Lamp Power (W)	System Power (W)	Initial Lumen (lm)	Base	Voltage (V)	Hour Rating	Beam Angle	CCT(K)	CRI	M.O.L. (inch)	Case QTY.
Non-Dimmable														
1762771	Y	VIV-T8BPSP4/9W/30/F	Bypass 2ft 9W G13 30K Frost Shatterproof	9	9	1150	G13	120-277	50,000	180	3000	83	24	25
1762356	Y	VIV-T8BPSP4/9W/35/F	Bypass 2ft 9W G13 35K Frost Shatterproof	9	9	1200	G13	120-277	50,000	180	3500	83	24	25
1762853	Y	VIV-T8BPSP4/9W/40/F	Bypass 2ft 9W G13 40K Frost Shatterproof	9	9	1200	G13	120-277	50,000	180	4000	83	24	25
1762534	Y	VIV-T8BPSP4/9W/50/F	Bypass 2ft 9W G13 50K Frost Shatterproof	9	9	1250	G13	120-277	50,000	180	5000	83	24	25
1762296	-	VIV-T8BPSP4/12W/30/F	Bypass 3ft 12W G13 30K Frost Shatterproof	12	12	1200	G13	120-277	50,000	180	3000	83	36	25
1762311	-	VIV-T8BPSP4/12W/35/F	Bypass 3ft 12W G13 35K Frost Shatterproof	12	12	1200	G13	120-277	50,000	180	3500	83	36	25
1762484	-	VIV-T8BPSP4/12W/40/F	Bypass 3ft 12W G13 40K Frost Shatterproof	12	12	1200	G13	120-277	50,000	180	4000	83	36	25
1762514	-	VIV-T8BPSP4/12W/50/F	Bypass 3ft 12W G13 50K Frost Shatterproof	12	12	1300	G13	120-277	50,000	180	5000	83	36	25
1762746	Y	VIV-T8BPSP4/12.5W/30/F	Bypass 4ft 12.5W G13 30K Frost Shatterproof	12.5	12.5	1650	G13	120-277	50,000	180	3000	83	48	25
1762342	Y	VIV-T8BPSP4/12.5W/35/F	Bypass 4ft 12.5W G13 35K Frost Shatterproof	12.5	12.5	1650	G13	120-277	50,000	180	3500	83	48	25
1762833	Y	VIV-T8BPSP4/12.5W/40/F	Bypass 4ft 12.5W G13 40K Frost Shatterproof	12.5	12.5	1750	G13	120-277	50,000	180	4000	83	48	25
1762527	Y	VIV-T8BPSP4/12.5W/50/F	Bypass 4ft 12.5W G13 50K Frost Shatterproof	12.5	12.5	1800	G13	120-277	50,000	180	5000	83	48	25
1763231	Y	VIV-T8BPSP4/14.5W/30/F	Bypass 4ft 14.5W G13 30K Frost Shatterproof	14.5	14.5	1900	G13	120-277	50,000	180	3000	83	48	25
1763313	Y	VIV-T8BPSP4/14.5W/35/F	Bypass 4ft 14.5W G13 35K Frost Shatterproof	14.5	14.5	1950	G13	120-277	50,000	180	3500	83	48	25
1763432	Y	VIV-T8BPSP4/14.5W/40/F	Bypass 4ft 14.5W G13 40K Frost Shatterproof	14.5	14.5	2000	G13	120-277	50,000	180	4000	83	48	25
1763512	Y	VIV-T8BPSP4/14.5W/50/F	Bypass 4ft 14.5W G13 50K Frost Shatterproof	14.5	14.5	2100	G13	120-277	50,000	180	5000	83	48	25
Dimmable														
1763425	Y	VIV-T8BPSP/18W/40/F/D	Bypass 4ft 18W G13 40K Frost Shatterproof Dimmable	18	18	1800	G13	120-277	50,000	180	4000	83	48	25
1763509	Y	VIV-T8BPSP/18W/50/F/D	Bypass 4ft 18W G13 50K Frost Shatterproof Dimmable	18	18	1900	G13	120-277	50,000	180	5000	83	48	25