



**LED FIXTURE**

**RIGID Series**

# LED Downlight With J-Box RGD-DLJ

LED downlight with integral junction box for easy and fast installation



## Features & Benefits

cETL listed, Energy Star

Size 6", 8" available

6" CRI ≥92, 97° Beam spread  
8" CRI ≥81, 94° Beam spread

120V input voltage

Dimmable

L70 @ 50,000 Hrs

6" Wet location approved  
8" Damp location approved

## Warranty

5-year limited warranty in commercial use from the date of purchase

Operating temperature range between -20°C and +40°C

## Product Specification

Ordering Code	Energy Star	Model Number	Description	Wattage (W)	Input Voltage (V)	Hour Rating	Beam Angle	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Wet Location	Damp Location	M.O.D. (inch)	Case QTY.
3662106	Y	RGD-DLJ/6/15W/30/D	Downlight with J-Box 6" 15W 30K Dimmable	15	120	50,000	97°	1000	3000	92	Y	-	7.3	12
3662107	Y	RGD-DLJ/6/15W/35/D	Downlight with J-Box 6" 15W 35K Dimmable	15	120	50,000	97°	1000	3500	92	Y	-	7.3	12
3662108	Y	RGD-DLJ/6/15W/40/D	Downlight with J-Box 6" 15W 40K Dimmable	15	120	50,000	97°	1000	4000	94	Y	-	7.3	12
3665117	Y	RGD-DLJ/8/35W/30/D	Downlight with J-Box 8" 35W 30K Dimmable	35	120	50,000	94°	2500	3000	81	-	Y	9.1	6
3665118	Y	RGD-DLJ/8/35W/35/D	Downlight with J-Box 8" 35W 35K Dimmable	35	120	50,000	94°	2500	3500	81	-	Y	9.1	6
3665119	Y	RGD-DLJ/8/35W/40/D	Downlight with J-Box 8" 35W 40K Dimmable	35	120	50,000	94°	2500	4000	81	-	Y	9.1	6

## Applications

Residential / Institution Lighting, School, Colleges, University and Hospitals, Supermarkets, Shops, Hotels, Conference Rooms, Office Lighting, Show Room, Corridor, Kitchen Room and etc.

## Ordering Information

Example: RGD-DLJ/6/15W/30/D

Family Name	Fixture Type	Size	Wattage	CCT (Kelvin)	Dimmable
RGD (Rigid)	DLJ (Downlight with J-Box)	6 (6") 8 (8")	35W 15W	40 (4000K) 35 (3500K) 30 (3000K)	D(Dimmable)

## Dimensional drawing

