

# LED LAMP

## VIVID Series



### VIV-PLS/BP



#### Features & Benefits

Bypass replacement for CFL PLS 2Pin (GX23)


350~700lm

50,000 hour life (L70)

High CRI (83+), 180° beam angle

Damp location approved

#### Dimensional drawing



#### Warranty & Cautions

3-year limited warranty in commercial use from the date of purchase

Operating temperature range between -20°C and +50°C

UL/cUL listed, FCC compliant, RoHS compliant

#### Product Specification

Ordering Code	Model Number	Description	Watts	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumen (lm)	CCT(K)	CRI	M.O.L. (inch)	Case QTY.
1751401	VIV-PLS/BP/4.5W/40/G23	PLS Bypass 4.5W 40K 2Pin	4.5	GX23	120/277	50,000	180	350	4000	83	5.79	50
1752417	VIV-PLS/BP/6W/40/GX23/S	PLS Bypass 6W 40K 2Pin	6	GX23	120/277	50,000	180	500	4000	83	6.75	50
1762161	VIV-PLS/BP/6W/27/2P	PLS Bypass 6W 27K 2Pin	6	GX23	120/277	50,000	180	500	2700	83	5.79	50
1762706	VIV-PLS/BP/6W/30/2P	PLS Bypass 6W 30K 2Pin	6	GX23	120/277	50,000	180	500	3000	83	5.79	50
1762320	VIV-PLS/BP/6W/35/2P	PLS Bypass 6W 35K 2Pin	6	GX23	120/277	50,000	180	500	3500	83	5.79	50
1762494	VIV-PLS/BP/6W/40/2P	PLS Bypass 6W 40K 2Pin	6	GX23	120/277	50,000	180	500	4000	83	5.79	50
1762162	VIV-PLS/BP/8W/27/2P	PLS Bypass 8W 27K 2Pin	8	GX23	120/277	50,000	180	700	2700	83	6.75	50
1762707	VIV-PLS/BP/8W/30/2P	PLS Bypass 8W 30K 2Pin	8	GX23	120/277	50,000	180	700	3000	83	6.75	50
1762321	VIV-PLS/BP/8W/35/2P	PLS Bypass 8W 35K 2Pin	8	GX23	120/277	50,000	180	700	3500	83	6.75	50
1762495	VIV-PLS/BP/8W/40/2P	PLS Bypass 8W 40K 2Pin	8	GX23	120/277	50,000	180	700	4000	83	6.75	50