

# LED LAMP

VIVID Series



## LED G9, G4 & MR11 Bulbs VIV-G9, VIV-G4, VIV-MR11




15,000hrs: 2-year; 25,000hrs: 3-year limited warranty

Operating temperature range -20° C ~ +40° C



Dimensional Drawing



### Features & Benefits

- cETLus listed
- High lumen design, CRI ≥80
- Dimmable (except MR11)
- 25,000 hrs average life\*
- Glass housing for MR11
- Suitable for use in totally enclosed luminaires\*
- Damp location approved\*

\*For applicable models, see product specification below

### Ordering Information Example: VIV-G9/4W/27/D

Family Name	Lamp Type	Wattage	CCT(K)	Dimmable
VIV (Vivid)	G9	2.5W	27 (2700K)	D (Dimmable)
VASO	G4	3W	30 (3000K)	Blank (Non-dimmable)
	MR11 (Glass housing)	4W	40 (4000K)	

### Product Specification

Ordering Code	Model Number	Watts	Replacement Halogen	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture	Damp Location	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
1751100	VIV-G9/4W/27/D	4	45W	G9	120	25,000	330°	450	2700	80	Y	Y	0.77	2.16	100
1751200	VIV-G9/4W/30/D	4	45W	G9	120	25,000	330°	450	3000	80	Y	Y	0.77	2.16	100
1751400	VIV-G9/4W/40/D	4	45W	G9	120	25,000	330°	450	4000	80	Y	Y	0.77	2.16	100
1751201	VIV-G4/2.5W/30/D	2.5	30W	G4	12	15,000	360°	300	3000	80	N	N	0.52	1.7	100
1751403	VIV-G4/2.5W/40/D	2.5	30W	G4	12	15,000	360°	300	4000	80	N	N	0.52	1.7	100
1751203	VASO-MR11/3W/30/FL/GU4	3	20W	GU4	12	25,000	30°	200	3000	80	Y	Y	1.38	1.5	100