



Key Features

- Die cast aluminum ballast housing with white powder coated finish for corrosion-resistance
- High temperature resistant polycarbonate (PC) hood
- C150, C200, C250 models are equipped with inner reflector
- The case of the ballast is part of the fixture to assure good heat sink and high reliability
- Simple latching hook system for quick and safe mounting

Electronic Features


- Round tubular induction lamp with high lighting efficiency and life span of 100,000hours
- Stable lumen output and high lumen maintenance
- CRI higher than 80, and IP rating IP43 (control gear)
- High power factor (>0.95), flickering free operation with low ballast loss and constant output

Applications


- Stadiums
- Warehouses
- Airports
- Workshops
- Railway stations
- Exhibition halls
- Supermarkets

Order Code	Model Number	Description	Lamp	Volts (V)	IP	Gear Box L xW xH (mm)	Alum Hood L xW xH (mm)	Lens	G.W. (kg)	Initial Lumens	UL cUL	CSA
3886523	ID-HB-ACR-C70	70W Ind.Hi-Bay,PC Hood,5000K&Blst	C70L	120-277	43	225x225x275	430x430x385	Acrylic	5.05	4900	Yes	-
3886536	ID-HB-ACR-C80	80W Ind.Hi-Bay,PC Hood,5000K&Blst	C80L	120-277	43	225x225x275	430x430x385	Acrylic	5.05	6000	Yes	-
3886510	ID-HB-ACR-C100	100W Ind.Hi-Bay,PC Hood,5000K&Blst	C100L	120-277	43	225x225x275	430x430x385	Acrylic	5.05	7500	Yes	-
3887504	ID-HB-ACR-C120	120W Ind.Hi-Bay,PC Hood,5000K&Blst	C120L	120-277	43	270x270x305	585x585x445	Acrylic	7.50	9000	Yes	-
3887514	ID-HB-ACR-C150	150W Ind.Hi-Bay,PC Hood,5000K&Blst	C150L	120-277	43	270x270x305	585x585x445	Acrylic	7.50	12000	Yes	-
3887522	ID-HB-ACR-C200	200W Ind.Hi-Bay,PC Hood,5000K&Blst	C200L	120-277	43	270x270x305	585x585x445	Acrylic	7.50	16000	Yes	-
3888107	ID-HB-ACR-C250	250W Ind.Hi-Bay,PC Hood,5000K&Blst	C250L	120-277	43	270x270x305	585x585x445	Acrylic	7.50	20000	Yes	-
3887523	ID-HB-ACR-C200/347V	200W Ind.Hi-Bay,PC Hood,5000K&Blst,347V	C200L	208-347	43	270x270x305	585x585x445	Acrylic	7.50	16000	-	Yes
3887535	ID-HB-ACR-C250/347V	250W Ind.Hi-Bay,PC Hood,5000K&Blst,347V	C250L	208-347	43	300x300x315	585x585x445	Acrylic	8.00	20000	-	Yes

*CCT(K) 5000K, Ambient Temp: -20 ~ +40, Hook Hanging Pole Installation, Average Life 100,000 hours.



Model Number	D	H	Note
ID-HB-ACR-C100	16.14(410)	23.62(400)	16"PC
ID-HB-ACR-C150	22.44(570)	27.24(510)	22"PC
ID-HB-ACR-C200	22.44(570)	27.24(510)	22"PC



Distributed by: