



### Key Features

- NSF/ANSI 2 Certified Shatter Shield prevents and protects in case of breakage
- 13W/27W with 1550/3300lm 4ft\*
- DLC Listed\*
- Suitable for splash zones of food equipment
- 50,000 hour life
- Direct replacement for T5 linear fluorescent
- Excellent distribution with 180° beam angle
- Fits into existing linear fixtures

\*Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at [www.designlights.org/qpl](http://www.designlights.org/qpl).

### Other information

- Operating temperature range between -20°C and +45°C
- UL/cUL listed, RoHS compliant
- 5-year limited warranty for DLC approved lamps / 3-year limited warranty for non-DLC in commercial and residential use (not recommended to use with ballast 7 years or older)



Conforms to NSF/ANSI 2

### Applications

- Offices
- Hospitality
- Retail
- Shopping Malls
- Restaurants

### General Usage

- Ideal replacement of Fluorescent T5 tubes

Order Code	Model Number	Description	DLC	Watts	Base	Voltage (V)	Initial Lumens	Beam Angle	CCT (K)	CRI	MOL (in)	CS QTY
<b>Linear Tubes</b>												
1762299	VIV-T5DF/13W/30/F	T5 Direct Fit 4ft 13W G5 30K Frost Shatterproof	-	13	G5	120-277,347	1350	180°	3000	≥83	48	25
1762313	VIV-T5DF/13W/35/F	T5 Direct Fit 4ft 13W G5 35K Frost Shatterproof	-	13	G5	120-277,347	1400	180°	3500	≥83	48	25
1762487	VIV-T5DF/13W/40/F	T5 Direct Fit 4ft 13W G5 40K Frost Shatterproof	-	13	G5	120-277,347	1450	180°	4000	≥83	48	25
1762516	VIV-T5DF/13W/50/F	T5 Direct Fit 4ft 13W G5 50K Frost Shatterproof	-	13	G5	120-277,347	1550	180°	5000	≥83	48	25
1764202	VIV-T5DF/27W/30/F	T5 Direct Fit 4ft 27W G5 30K Frost Shatterproof		27	G5	120-277,347	3100	180°	3000	≥83	48	25
1764302	VIV-T5DF/27W/35/F	T5 Direct Fit 4ft 27W G5 35K Frost Shatterproof		27	G5	120-277,347	3150	180°	3500	≥83	48	25
1764402	VIV-T5DF/27W/40/F	T5 Direct Fit 4ft 27W G5 40K Frost Shatterproof		27	G5	120-277,347	3200	180°	4000	≥83	48	25
1764502	VIV-T5DF/27W/50/F	T5 Direct Fit 4ft 27W G5 50K Frost Shatterproof		27	G5	120-277,347	3300	180°	5000	≥83	48	25

### Dimensions



PLEASE CONSULT OUR LIST OF COMPATIBLE BALLASTS: ([HTTP://WWW.TUROLIGHT.COM/DCL](http://www.turolight.com/dcl))  
 WE RECOMMEND CHECKING THE BRAND AND AGE OF THE EXISTING BALLAST BEFORE INSTALLATION.  
 SOCKETS MUST BE SHUNTED AND IN NEW CONDITION.

How to read: 

VIV	/	T8	DF	/	27W	/	40	/	F
LED Class		Lamp Type	Direct Fit		Wattage		CCT(K)		Frost