



### Physical Features

- Protective architectural dark bronze power coating to ensure long lasting performance even in harsh environment
- Compact and light weighted, ideal for confined spaces
- Wet location rated for outdoor application
- IES type V for optimized light distribution
- Optional installation of Trunnion Mount and Wall Mount



### Application

Building facades, Displays, Landscaping, Security lighting, Walkways and other work areas.

### Electronic Features

- Light output from 1500 lumen up to 5400 lumen
- High lumen efficient LED lamps with 70% energy saving
- Long life span of 50,000hours to reduce significantly maintenance cost
- 15W, 30W, 45W Replaces 50W, 100W, 150W PSMH
- CRI ≥ 70

### Other information

- cUL listed and DLC listed
- 5-year limited warranty for DLC approved

### Installation



KNC - Knuckle



WM - Wall Mount



YK - U-Bracket (Trunnion Mount)

Order Code	Model Number	Description	DLC	Watts	Volts (V)	Hours Rating	Optics/ Distribution	Init. Lm	CCT(K)	CRI	Wet Loc	Dimensions LxWxH (mm)
3663100	SSL-SFL1/15W/50/UNV/DB/KNC	SSL 15W Slim Flood I, 50K, 120-277V, Dark Bronze, Knuckle		15	120-277	50,000	Type V	1500	5000K	70	Y	4.72 X 2.95 X 1.27
3665113	SSL-SFL1/30W/50/UNV/DB/KNC	SSL 30W Slim Flood I, 50K, 120-277V, Dark Bronze, Knuckle		30	120-277	50,000	Type V	3000	5000K	70	Y	7.08 X 4.42 X 1.61
3665114	SSL-SFL1/45W/50/UNV/DB/KNC	SSL 45W Slim Flood I, 50K, 120-277V, Dark Bronze, Knuckle		45	120-277	50,000	Type V	5400	5000K	70	Y	8.26 X 5.16 X 2.45

Ambient Operating Temperature -40°C ~ +45°C; For the latest stock status please refer to your price list or send us an email at [sales@turolight.com](mailto:sales@turolight.com)

### Ordering Information

SSL	SFL1	15W	50	UNV	DB	KNC
Family	Fixture Style	Wattage	CCT (K)	Voltage	Body Finish	Bracket Type
	SFL1 - Slim Flood I	15W 30W 45W	40 - 4000K 50 - 5000K	UNV - 120-277V	DB - Dark Bronze	KNC - Knuckle WM - Wall Mounting YK - U-Bracket (Trunnion Mount)