



Key Features

- 12W/1100 Lumens
- Non-dimmable
- 12W replaces 100W/130V incandescent
- Suitable for damp locations
- Light weight design
- Even light distribution
- No UV, no infrared and mercury free

Applications

- Residential
- Hospitality
- Retail
- Art galleries and museums
- Shopping Malls
- Offices
- Restaurants

Other information

- Operating temperature range between -20°C and +45°C
- UL/cUL listed, FCC compliant
- 2-year limited warranty from the date of purchase

General Usage

- Table/Floor lamps
- Wall Sconces
- Pendants

Order Code	Model Number	Watts	Base	Volts	Hour Rating	Beam Angle	Initial Lumens	CCT (K)	CRI	M.O.L. (inch)	Case Qty.
1732102	PV-A19/12W/27	12	E26	120	15,000	220°	1100	2700	80	4.3	40
1732202	PV-A19/12W/30	12	E26	120	15,000	220°	1100	3000	80	4.3	40
1732302	PV-A19/12W/40	12	E26	120	15,000	220°	1100	4000	80	4.3	40
1732502	PV-A19/12W/50	12	E26	120	15,000	220°	1100	5000	80	4.3	40
1732101	PV-A19/9W/27	9	E26	120	10,000	220°	800	2700	78	4.3	40
1732201	PV-A19/9W/30	9	E26	120	10,000	220°	800	3000	78	4.3	40
1732401	PV-A19/9W/40	9	E26	120	10,000	220°	800	4000	78	4.3	40
1732501	PV-A19/9W/50	9	E26	120	10,000	220°	800	5000	78	4.3	40
1732100	PV-A19/5.5W/27	5.5	E26	120	10,000	220°	450	2700	78	4.3	40
1732200	PV-A19/5.5W/30	5.5	E26	120	10,000	220°	450	3000	78	4.3	40
1732400	PV-A19/5.5W/40	5.5	E26	120	10,000	220°	450	4000	78	4.3	40
1732500	PV-A19/5.5W/50	5.5	E26	120	10,000	220°	450	5000	78	4.3	40

For the latest stock status please refer to your price list or send us an email at sales@turolight.com

Dimensions

How to read: PV - A19 / 12W / 30

LED Class	Lamp Type	Wattage	CCT(K)
-----------	-----------	---------	--------

Distributed by: