

Super Arc™

Metal Halide Lamps



ED28

ED37

BT56

BT37

ED17

Features and Benefits

- 10,000 to 20,000-hour life
- Available in 3700K and 4000K
- 65-70 CRI
- Energy efficient
- High lumen output
- Compact arc size
- Distributes light evenly
- Reduces maintenance and replacement
- 1 to 2-year warranty

Applications

- Sports arenas
- Tennis courts
- Billboard signage
- Industrial applications
- Canopy lighting
- Car dealerships
- Security lighting
- Convention centers
- Gas stations
- Parking lots/garages
- Big box retail
- Airport lighting

Super Arc Metal Halide Lamps Offer Superior White Light

Litetronics Super Arc™ Metal Halide lamps are a superior choice for efficient, long-lasting lighting in most general applications. Super Arc lamps provide a bright, white light. The high 65-70 CRI helps bring out colors and textures, while improving visual acuity.

Super Arc Metal Halide lamps, available in clear or with phosphor coating, have an average life of 10,000 to 20,000 hours. The compact arc size of Super Arc lamps improves the lamps' effectiveness, continuing the Litetronics tradition of producing the highest quality lamps available. For superior lighting that lasts, Super Arc Metal Halide lamps are the clear choice.

 **TUROLIGHT**®
WWW.TUROLIGHT.COM

Toll Free: 1 (877) 736-0447 • Fax: (416) 736-4890
Email: info@turolight.com • Website: www.turolight.com

Super Arc™ Metal Halide Lamps



ED17



ED28



ED37



BT37



BT56

| LAMP | WATTS | BULB TYPE | BASE | DESCRIPTION | ORDERING CODE | QTY/ CASE | AVERAGE RATED LIFE | ANSI CODE | CRI | CORRELATED COLOR TEMP(K) | INITIAL LUMENS | MEAN LUMENS | M.O.L.** |
|------|-------|-----------|------|-----------------|---------------|-----------|--------------------|-----------|-----|--------------------------|----------------|-------------|----------|
| ED17 | 175 | ED17 | MED | MH175 U CL MED | L-835 | 12 | 10,000 | M57 | 65 | 4000 | 14,000 | 9,295 | 5.44" |
| ED28 | 175 | ED28 | MOG | MH175 U CL MOG | L-830 | 12 | 12,000 | M57 | 65 | 4000 | 14,000 | 11,200 | 8.30" |
| | 250 | ED28 | MOG | MH250 U CL MOG | L-845 | 12 | 12,000 | M58 | 65 | 4000 | 21,000 | 17,935 | 8.30" |
| ED37 | 400 | ED37 | MOG | MH400 U CL MOG | L-850 | 12 | 20,000 | M59 | 65 | 4000 | 36,000 | 28,000 | 11.02" |
| | 400 | ED37 | MOG | MH400 U CT MOG | L-860 | 12 | 20,000 | M59 | 70 | 3700 | 36,000 | 28,800 | 11.02" |
| BT56 | 1000 | BT56 | MOG | MH1000 U CL MOG | L-870 | 4 | 12,000 | M47 | 65 | 4000 | 110,000 | 86,000 | 15.38" |

Open Fixture Metal Halide

| LAMP | WATTS | BULB TYPE | BASE | DESCRIPTION | ORDERING CODE | QTY/ CASE | AVERAGE RATED LIFE | ANSI CODE | CRI | CORRELATED COLOR TEMP(K) | INITIAL LUMENS | MEAN LUMENS | M.O.L.** |
|------|-------|-----------|------|-------------------|---------------|-----------|--------------------|-----------|-----|--------------------------|----------------|-------------|----------|
| ED37 | 400 | ED37 | MOG | MP400 BU CL MOG 0 | L-876 | 12 | 20,000 | M59 | 65 | 4000 | 32,000 | 26,000 | 11.50" |

Compact Metal Halide

| LAMP | WATTS | BULB TYPE | BASE | DESCRIPTION | ORDERING CODE | QTY/ CASE | AVERAGE RATED LIFE | ANSI CODE | CRI | CORRELATED COLOR TEMP(K) | INITIAL LUMENS | MEAN LUMENS | M.O.L.** |
|------|-------|-----------|------|-------------------|---------------|-----------|--------------------|-----------|-----|--------------------------|----------------|-------------|----------|
| ED28 | 400 | ED28 | MOG | MH400 U CL MOG R | L-855 | 12 | 20,000 | M59 | 70 | 4000 | 36,000 | 28,000 | 8.30" |
| BT37 | 1000 | BT37 | MOG | MH1000 U CL MOG R | L-856 | 12 | 12,000 | M47 | 65 | 4000 | 110,000 | 96,000 | 11.50" |

** Maximum Overall Length (in inches)



Toll Free: 1 (877) 736-0447 • Fax: (416) 736-4890
 Email: info@turolight.com • Website: www.turolight.com

TUROLIGHT®
 WWW.TUROLIGHT.COM