



Physical Features

- Energy Star listed
- Airtight Structure - to reduce heating and cooling cost
- Type IC Rated – approved for direct contact with insulation
- Isolated internal driver in junction box – fast and easy to install
- Slim design allows it to be installed in the plenum ceiling space
- Dimmable
- Damp location approved



Application

Residential / Institution Lighting
 School, Colleges, University and
 Hospitals, Supermarkets, Shops,
 Hotels, Conference Rooms, Office Lighting,
 Show Room, Corridor, Kitchen Room etc.

Electronic Features

- 1100 lumen stable lumen output
- 10W, 15W Replaces 50W, 75W halogen
- Long life span of 35,000 hours
- High CRI (80+)
- Working temperature ranges from -25° to +40°

Other information

- cETL ETL listed and ES listed
- 3-year limited warranty

Order Code	Model Number	Description	ES	Watts	Volts	Hour Rating	Beam Angle	Init. Lum.	CCT (K)	CRI	Damp Loc	M.O.D. (inch)	CS Qty.
1762774	RGD-RK/4/SP/10W/30/D	RIGID 4" Slim Panel Down Light 10W 30K Dimmable		10	120	35,000	120°	650	3000	80	Y	4.73	30
1762856	RGD-RK/4/SP/10W/40/D	RIGID 4" Slim Panel Down Light 10W 40K Dimmable		10	120	35,000	120°	650	4000	80	Y	4.73	30
1762775	RGD-RK/6/SP/15W/30/D	RIGID 6" Slim Panel Down Light 15W 30K Dimmable		15	120	35,000	120°	1100	3000	80	Y	7.09	30
1762857	RGD-RK/6/SP/15W/40/D	RIGID 6" Slim Panel Down Light 15W 40K Dimmable		15	120	35,000	120°	1200	4000	80	Y	7.09	30

Ambient Operating Temperature -25°C ~ +40°C

For the latest stock status please refer to your price list or send us an email at sales@turolight.com

How our Model No. Works:

Ordering Information

RGD	RK	4	SP	10W	30	D
Family	Reflector Type	Size	Slim Panel	Wattage	CCT(K)	Dimmable
	RK - Retrofit Kit	4 inch 6 inch		10W 15W	30K 40K	