





LED TRACK HEAD

Unique design with it's sleek appearance. Over 50% energy saving compare to ceramic metal halide thanks to the high efficacy up to 115lm per watt.

The wide range of accessories and interchangeable lens affords it even greater choice and flexibility.





Features & Benefits

Anti-glare, over 100 LPW

Color finish (White, Silver, Black)

TRIAC/ELV Dimmable: Smooth dimming range from 100% to 10%

Die casting aluminum housing

Precise light distribution

Macadam 3 SDCM

Ultraviolet (UV) + Infrared (IR) free light

Passive cooling system without fans

Warranty


5-year limited warranty in commercial use from the date of purchase $% \left(1\right) =\left(1\right) \left(1\right)$

Operating temperature range between -20°C and +40°C

Applications

Residential, Retail, Art-gallery, Museum, Automotive and Parking, Education, Government, Healthcare, Hospitality, Offices and Banks, etc.

Dimensional drawing



	D	L	Н		
S (Size Small)	2 3/8"	3 3/4"	5 5/8"		
M (Size Medium)	4"	4 1/4"	6 3/4"		
L (Size Large)	43/8"	5 1/2"	7 1/2"		



LED TRACK HEAD

TRK-PIN

Ordering Information Example: TRK-PIN/L/34W/120/30K/24/D/WH/H

Family Name	Fixture Type	Size	Wattage	Voltage (V)	ССТ	Beam Angle	Dimmable	Color Finish	MTD Adapter	Lumen
TRK (Track)	PIN (Pinch)	S (Small)	10W	120 (120V)	30K (3000K)	24 (24°) 40 (40°) 60 (60°)	D (Dimmable)	WH (White) SL (Silver) BK (Black)	Н (Н Туре)	820
		M (Medium)	14W 22W							1340 2030
		L (Large)	34W							3200

Product Specification

DLC	Model Number	Wattage (W)	Input Voltage (V)	CCT Optial	Beam Angle	Power Factor	Dimmable	Lumen Flux	CRI Optial
Yes	TRK-PIN/L/34W/120/30K/24/D/WH/H	34	120	3000K	24°, 40°, 60°	>0.95	Yes	3200lm (3000K)	CRI82