

LED LAMP

VIVID Series




VIV-T5DF4



Features & Benefits

DLC approved	NSF/ANSI 2 Certified ¹
All glass construction , aluminium end caps	Suitable for splash zones of food equipment
50,000 hour life (L70)	Fits into existing linear fixtures
220° Beam angle, High CRI (83+)	Compatible with most program start ballast ²
Replaces T5 HO & T5 HE	¹ Need to work with NSF certified lighting fixtures ² Contact your sales person or check www.turolight.com for ballast compatibility list

Dimensional drawing



Warranty & Cautions

5-year limited warranty for DLC listed lamps / 3-year limited warranty for non-DLC*

Bulb wall temperature range between -20°C and +45°C

Not recommended to use with ballast 5 years or older

*Please check the "Turolight LED Limited Warranty" for details

Product Specification

Ordering Code	DLC	Model Number	Description	Wattage		Lum/W	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumen (lm)	CCT(K)	CRI	M.O.L. (inch)	Case QTY.
				Lamp Power (W)	System Power (W)										
1764212	Y	VIV-T5DF4/25W/30/F	T5 Direct Fit 4ft 25W G5 30K Frost	25	28	112.5	G5	120-277, 347	50,000	220	3150	3000	83	48	25
1764307	Y	VIV-T5DF4/25W/35/F	T5 Direct Fit 4ft 25W G5 35K Frost	25	28	112.5	G5	120-277, 347	50,000	220	3150	3500	83	48	25
1764410	Y	VIV-T5DF4/25W/40/F	T5 Direct Fit 4ft 25W G5 40K Frost	25	28	114.3	G5	120-277, 347	50,000	220	3200	4000	83	48	25
1764509	Y	VIV-T5DF4/25W/50/F	T5 Direct Fit 4ft 25W G5 50K Frost	25	28	117.9	G5	120-277, 347	50,000	220	3300	5000	83	48	25
1762022	Y	VIV-T5DF4/13W/30/F	T5 Direct Fit 4ft 13W G5 30K Frost	13	16	112.5	G5	120-277, 347	50,000	220	1800	3000	83	48	25
1762366	Y	VIV-T5DF4/13W/35/F	T5 Direct Fit 4ft 13W G5 35K Frost	13	16	112.5	G5	120-277, 347	50,000	220	1800	3500	83	48	25
1762888	Y	VIV-T5DF4/13W/40/F	T5 Direct Fit 4ft 13W G5 40K Frost	13	16	115.6	G5	120-277, 347	50,000	220	1850	4000	83	48	25
1762552	Y	VIV-T5DF4/13W/50/F	T5 Direct Fit 4ft 13W G5 50K Frost	13	16	126.7	G5	120-277, 347	50,000	220	1900	5000	83	48	25

Ordering Information Example: VIV-T5DF4/25W/30/F

LED CLASS	LAMP TYPE	DIRECT FIT	WATTAGE	CCT(K)	FROST
VIV (Vivid)	T5	DF4 (Direct Fit, 4 th version)	25W 13W	50 (5000K) 40 (4000K) 35 (3500K) 30 (3000K)	F (Frost)