

LED LAMP

VIVID Series

DirectFit T5 Lamp



VIV-T5DFSP4



Features & Benefits

DLC approved ¹	Suitable for splash zones of food equipment
Direct Fit , Frost Shatterproof	50,000 hour life (L70)
NSF/ANSI 2 Certified ²	Fits into existing linear fixtures
Replaces T5 HO & T5 HE	Compatible with most program start ballast ³
180° Beam angle, High CRI (83+)	

¹For applicable models, see product specification below
²Need to work with NSF certified lighting fixtures
³Contact your sales person or check www.turolight.com for ballast compatibility list

Dimensional drawing



Warranty & Cautions

5-year limited warranty for DLC listed lamps / 3-year limited warranty for non-DLC*

Bulb wall temperature range between -20°C and +45°C

Not recommended to use with ballast 5 years or older

*Please check the "Turolight LED Limited Warranty" for details

Product Specification

Ordering Code	DLC	Model Number	Description	Wattage		Lum/W	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumen (lm)	CCT(K)	CRI	M.O.L. (inch)	Case QTY.
				Lamp Power (W)	System Power (W)										
Replaces T5 HO															
1762351	-	VIV-T5DFSP4/9W/35/F	Direct Fit 2ft 9W G5 35K Frost Shatterproof	9	12	83.3	G5	120-277, 347	50,000	180	1000	3500	83	24	25
1762848	-	VIV-T5DFSP4/9W/40/F	Direct Fit 2ft 9W G5 40K Frost Shatterproof	9	12	83.3	G5	120-277, 347	50,000	180	1000	4000	83	24	25
1762529	-	VIV-T5DFSP4/9W/50/F	Direct Fit 2ft 9W G5 50K Frost Shatterproof	9	12	83.3	G5	120-277, 347	50,000	180	1000	5000	83	24	25
1763314	-	VIV-T5DFSP4/18W/35/F	Direct Fit 3ft 18W G5 35K Frost Shatterproof	18	21	81.0	G5	120-277, 347	50,000	180	1700	3500	83	36	25
1763434	-	VIV-T5DFSP4/18W/40/F	Direct Fit 3ft 18W G5 40K Frost Shatterproof	18	21	81.0	G5	120-277, 347	50,000	180	1700	4000	83	36	25
1763513	-	VIV-T5DFSP4/18W/50/F	Direct Fit 3ft 18W G5 50K Frost Shatterproof	18	21	81.0	G5	120-277, 347	50,000	180	1700	5000	83	36	25
1764208	Y	VIV-T5DFSP4/25W/30/F	Direct Fit 4ft 25W G5 30K Frost Shatterproof	25	28	112.5	G5	120-277, 347	50,000	180	3150	3000	83	48	25
1764304	Y	VIV-T5DFSP4/25W/35/F	Direct Fit 4ft 25W G5 35K Frost Shatterproof	25	28	112.5	G5	120-277, 347	50,000	180	3150	3500	83	48	25
1764404	Y	VIV-T5DFSP4/25W/40/F	Direct Fit 4ft 25W G5 40K Frost Shatterproof	25	28	114.3	G5	120-277, 347	50,000	180	3200	4000	83	48	25
1764505	Y	VIV-T5DFSP4/25W/50/F	Direct Fit 4ft 25W G5 50K Frost Shatterproof	25	28	117.9	G5	120-277, 347	50,000	180	3300	5000	83	48	25
Replaces T5 HE															
1762352	-	VIV-T5DFSP4/6W/35/F	Direct Fit 2ft 6W G5 35K Frost Shatterproof	6	9	100.0	G5	120-277, 347	50,000	180	900	3500	83	24	25
1762849	-	VIV-T5DFSP4/6W/40/F	Direct Fit 2ft 6W G5 40K Frost Shatterproof	6	9	105.6	G5	120-277, 347	50,000	180	950	4000	83	24	25
1762530	-	VIV-T5DFSP4/6W/50/F	Direct Fit 2ft 6W G5 50K Frost Shatterproof	6	9	111.1	G5	120-277, 347	50,000	180	1000	5000	83	24	25
1762353	-	VIV-T5DFSP4/9W/35/F/3FT	Direct Fit 3ft 9W G5 35K Frost Shatterproof	9	12	87.5	G5	120-277, 347	50,000	180	1050	3500	83	36	25
1762850	-	VIV-T5DFSP4/9W/40/F/3FT	Direct Fit 3ft 9W G5 40K Frost Shatterproof	9	12	100.0	G5	120-277, 347	50,000	180	1200	4000	83	36	25
1762531	-	VIV-T5DFSP4/9W/50/F/3FT	Direct Fit 3ft 9W G5 50K Frost Shatterproof	9	12	108.3	G5	120-277, 347	50,000	180	1300	5000	83	36	25
1762793	Y	VIV-T5DFSP4/13W/30/F	Direct Fit 4ft 13W G5 30K Frost Shatterproof	13	16	112.5	G5	120-277, 347	50,000	180	1800	3000	83	48	25
1762354	Y	VIV-T5DFSP4/13W/35/F	Direct Fit 4ft 13W G5 35K Frost Shatterproof	13	16	112.5	G5	120-277, 347	50,000	180	1800	3500	83	48	25
1762851	Y	VIV-T5DFSP4/13W/40/F	Direct Fit 4ft 13W G5 40K Frost Shatterproof	13	16	115.6	G5	120-277, 347	50,000	180	1850	4000	83	48	25
1762532	Y	VIV-T5DFSP4/13W/50/F	Direct Fit 4ft 13W G5 50K Frost Shatterproof	13	16	126.7	G5	120-277, 347	50,000	180	1900	5000	83	48	25