

LED LAMP ARTISAN



A19, B10, ST19, T9

LOW
non visible
FLICKER




Features & Benefits

- Reduced flicker down to 10%
- Compare to 6.6% traditional incandescent
 - Far below California T20 standard 30%
 - Significantly improve light quality
 - Optimize eye comfort

- With clear or amber glass cover
- Dimmable, High CRI (80+)
- 15,000 hour average life span
- Rated for damp locations

Dimensional drawing



Warranty & Cautions

2-year limited warranty in commercial use from the date of purchase

Operating temperature range between -20°C and +40°C

Product Specification

| Ordering Code | Model Number | Product Description | Watts (W) | Replacement Filament | Replacement Incandescent | Base | Voltage (V) | Hour Rating | Beam Angle | Initial Lumens (lm) | CCT(K) | CRI | Damp LOC. | M.O.L. (inch) | Case QTY. |
|---------------|-------------------------|--|-----------|----------------------|--------------------------|------|-------------|-------------|------------|---------------------|--------|-----|-----------|---------------|-----------|
| 1772110 | AR-A19LF/8W/27/D/C | A19 Low Flicker 8W 27K Dimmable Clear | 8 | - | 60W | E26 | 120 | 15,000 | 330° | 800 | 2700 | 80 | Y | 4.29 | 40 |
| 1772202 | AR-A19LF/8W/30/D/C | A19 Low Flicker 8W 30K Dimmable Clear | 8 | - | 60W | E26 | 120 | 15,000 | 330° | 800 | 2700 | 80 | Y | 4.29 | 40 |
| 1771203 | AR-B10LF/4W/30/E12/D/C | B10 Low Flicker 4W 30K E12 Dimmable Clear | 4 | - | 40W | E12 | 120 | 15,000 | 330° | 350 | 3000 | 80 | Y | 3.78 | 50 |
| 1771925 | AR-B10LF/4W/22/E12/D/A | B10 Low Flicker 4W 22K E12 Dimmable Amber | 4 | 40W | - | E12 | 120 | 15,000 | 330° | 280 | 2200 | 80 | Y | 3.78 | 50 |
| 1772111 | AR-ST19LF/5W/27/D/C | ST19 Low Flicker 5W 27K Dimmable Clear | 5 | - | 60W | E26 | 120 | 15,000 | 330° | 500 | 2700 | 80 | Y | 5.39 | 20 |
| 1772203 | AR-ST19LF/5W/30/D/C | ST19 Low Flicker 5W 30K Dimmable Clear | 5 | - | 60W | E26 | 120 | 15,000 | 330° | 500 | 3000 | 80 | Y | 5.39 | 20 |
| 1771404 | AR-ST19LF/5W/40/D/C | ST19 Low Flicker 5W 40K Dimmable Clear | 5 | - | 60W | E26 | 120 | 15,000 | 330° | 500 | 4000 | 80 | Y | 5.39 | 20 |
| 1772908 | AR-ST19LF/5W/22/D/A | ST19 Low Flicker 5W 22K Dimmable Amber | 5 | 60W | - | E26 | 120 | 15,000 | 330° | 400 | 2200 | 80 | Y | 5.39 | 20 |
| 1771205 | AR-T6LF/2.5W/30/E12/D/C | T6 Low Flicker 2.5W 30K E12 Dimmable Clear | 2.5 | - | 25W | E12 | 120 | 15,000 | 330° | 200 | 3000 | 80 | Y | 3.84 | 50 |
| 1771140 | AR-T9LF/4W/27/D/C | T9 Low Flicker 4W 27K Dimmable Clear | 4 | - | 40W | E26 | 120 | 15,000 | 330° | 350 | 2700 | 80 | Y | 5.71 | 50 |
| 1771206 | AR-T9LF/4W/30/D/C | T9 Low Flicker 4W 30K Dimmable Clear | 4 | - | 40W | E26 | 120 | 15,000 | 330° | 350 | 3000 | 80 | Y | 5.71 | 50 |
| 1771207 | AR-T14LF/5W/30/D/C | T14 Low Flicker 5W 30K Dimmable Clear | 5 | - | 60W | E26 | 120 | 15,000 | 330° | 500 | 3000 | 80 | Y | 4.71 | 50 |

Ordering Information Example: AR-A19LF/8W/27/D/C

| LED CLASS | LAMP TYPE | WATTAGE | CCT(K) | BASE | DIMMABLE | COVER |
|--------------|--|------------------------|--|--------------------------|--------------|------------------------|
| AR (Artisan) | A19LF (A19 Low Flicker) B10LF (B10 Low Flicker) ST19LF (ST19 Low Flicker) T6LF (T6 Low Flicker) T9LF (T9 Low Flicker) T14LF (T14 Low Flicker) | 8W 5W 4W 2.5W | 30 (3000K) 27 (2700K) 22 (2200K) | E12 (E12) Blank (E26) | D (dimmable) | C (Clear) A (Amber) |