



Key Features

- High Lumens 685lm
75W halogen replacement
- High CRI 90 available
- Energy Star Listed
- Suitable for damp location
- Suitable for enclosed fixture
- 25,000 hour average life
- Reduces energy consumption up to 80%
- No UV, no infrared and mercury free

Other information

- Operating temperature range between -20°C and +40°C
- UL/cUL listed, FCC compliant, RoHS compliant
- 3-year limited warranty in commercial and residential use



Applications


- Premium Retail
- Art Galleries and Museums
- High End Boutiques
- Restaurants
- Shopping Malls

General Usage

- Recessed Down Lights/Pot Lights
- Track Lights
- Specialty
- Under Cabinet Lights
- Display Cases

Order Code	Model Number	ES	Watts	Base	Volts	Hour Rating	Beam Angle	Initial Lumens	CCT (K)	CRI	C.B.C.P.	M.O.L. (inch)	Case Qty.
1782225	HD-MR16/9W/30/SP15/GU5.3/D/HL		9	GU5.3	12	25,000	15°	685	3000	80	6800	2.0	50
1782226	HD-MR16/9W/30/FL25/GU5.3/D/HL		9	GU5.3	12	25,000	25°	685	3000	80	3200	2.0	50
1782227	HD-MR16/9W/30/FL35/GU5.3/D/HL		9	GU5.3	12	25,000	35°	685	3000	80	1850	2.0	50
1782228	HD-MR16/9W/30/FL35/GU5.3/D/I90		9	GU5.3	12	25,000	35°	565	3000	90	1463	2.0	50

Dimensions



How to read:

HD - MR16 / 9W / 30 / SP15 / GU5.3 / D / **
LED Class Lamp Type Wattage CCT(K) Beam Angle Lamp Base Dimmable High lumens/High CRI

Distributed by: