

# LED FIXTURE

## SSL Series

# LED High Bay SSL-UHB

LED High Bay Lighting Fixture with Magnesium Alloy heatsink



### Features & Benefits

cETC listed	LG LED Chip
System light efficacy 130 LPW	CRI≥80, L70@ 100,000 Hrs
Magnesium Alloy material, lighter in weight	Voltage 120-277V and 347/480V
Tilted heat sink back design for easy wash-off	120° Beam spread
Superior electrical and thermal conductivity	1-10V dimming
Durable TGIC painting <b>White</b> finish, better for tough weather conditions	IP65 rated, wet location
10 ft power cord	


### Warranty

5-year limited warranty in commercial use from the date of purchase  
 Operating temperature range between -40°C and +50°C

### Applications

Warehouse/Manufacturing Facilities, Convention Centers/Sporting Arenas  
 Big-Box Retail Stores, Cold Storage Facilities, Gymnasiums

### Dimensional drawing



	DIA	H
<b>100W</b>	9.65"	7.24"
<b>150W</b>	11.02"	7.95"
<b>200W</b>	11.81"	8.23"
<b>240W</b>	11.81"	8.23"

# LED High Bay

## SSL-UHB

### Ordering Information Example: SSL-UHB/100W/50/UNV/HK/D

Family Name	Fixture Type	Wattage	CCT	Voltage (V)	Mounting	Dimmable	Options
SSL (Solid State Lighting)	UHB (Universal High Bay)	100W 150W 200W 240W	50 (5000K)	UNV (120-277V) HVU (347/480V)	HK (Hook Mounting)	D (1-10V dimming)	SSL-UHB/14/AL/HOOD/90D SSL-UHB/16/PC/HOOD/70D SSL-UHB/PC/DIFFUSER/17UP SSL-UHB/JBOX SSL-UHB/SENSOR SSL-UHB/IP65JBOX



HK (Hook Mounting)

### Product Specification

Ordering Code	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Dimension DIA×H(inch)	Case QTY.	
3666123	SSL-UHB/100W/50/UNV/HK/D	100	120-277V	100,000	13,000	5000	≥80	9.65×7.24	1	
3666228	SSL-UHB/100W/50/HVU/HK/D	100	347/480V	100,000	13,000	5000	≥80	9.65×7.24	1	
3667115	SSL-UHB/150W/50/UNV/HK/D	150	120-277V	100,000	20,705	5000	≥80	11.02×7.95	1	
3667217	SSL-UHB/150W/50/HVU/HK/D	150	347/480V	100,000	19,878	5000	≥80	11.02×7.95	1	
3667116	SSL-UHB/200W/50/UNV/HK/D	200	120-277V	100,000	27,070	5000	≥80	11.81×8.23	1	
3667218	SSL-UHB/200W/50/HVU/HK/D	200	347/480V	100,000	26,180	5000	≥80	11.81×8.23	1	
3667129	SSL-UHB/240W/50/UNV/HK/D	240	120-277V	100,000	36,000	5000	≥80	11.81×8.23	1	
3667231	SSL-UHB/240W/50/HVU/HK/D	240	347/480V	100,000	36,000	5000	≥80	11.81×8.23	1	
3660041	SSL-UHB/14/AL/HOOD/90D	90 Degree 14" Aluminium Hood								
3660042	SSL-UHB/16/PC/HOOD/70D	70 Degree 16" Polycarbonate Hood								
3660043	SSL-UHB/PC/DIFFUSER/17UP	180 Degree Polycarbonate Diffuser w/ 17% up light.								
3660044	SSL-UHB/JBOX	Junction Box for Conduit Mtg, Through Wiring, White Finish								
3660045	SSL-UHB/SENSOR	Sensor, 120-277V, Daylight & Motion sensing.								
3660046	SSL-UHB/IP65JBOX	IP65 Junction Box (use with Sensor) applications.								



90° Aluminium Reflector  
SSL-UHB/14/AL/HOOD/90D



70° PC Reflector  
SSL-UHB/16/PC/HOOD/70D



180° PC Lens  
SSL-UHB/PC/DIFFUSER/17UP



Junction Box  
SSL-UHB/JBOX



Sensor  
SSL-UHB/SENSOR



Junction Box (use with sensor)  
SSL-UHB/IP65JBOX