



LED FIXTURE

SSL Series

LED Slim Flood SSL-SFL1

The Mini LED floodlights replace 50W, 100W and 150W pulse start metal halide floodlights
Applications include building facades, landscaping, security lighting and walkways.



Knuckle Mounting



Features & Benefits

CUL listed

Available with lumen outputs from 1,500 to 5,400 lumens
Consumes 15W-45W to replace 50W-150W MH light

Rugged Die-cast aluminum housing

UV resistant dark bronze powder body finish

Traditional 1/2" NPS threaded adjustable knuckle mounting
Trunnion and wall mount (only for 30W & 45W) optional

Wet location rated

Voltage 120-277V

CRI≥70, L70 @ 50,000 Hrs

Warranty

5-year limited warranty in commercial use from the date of purchase

Operating temperature range between -40°C and +45°C

Product Specification

Ordering Code	Model Number	Description	Wattage (W)	Input Voltage (V)	Hour Rating	Beam Pattern NEMA	Initial Delivered Lumens (lm)	CCT (K)	CRI	Dimension L×W×H(inch)	Case QTY.
3663100	SSL-SFL1/15W/50/UNV/DB/KNC	15W, 50K, 120-277V, Dark Bronze, Knuckle	15	120-277	50,000	7H×7V	1500	5000K	70	4.72 X 2.95 X 1.27	1
3665113	SSL-SFL1/30W/50/UNV/DB/KNC	30W, 50K, 120-277V, Dark Bronze, Knuckle	30	120-277	50,000	7H×7V	3000	5000K	70	7.08 X 4.42 X 1.61	1
3664122	SSL-SFL1/30W/50/UNV/DB/WM	30W, 50K, 120-277V, Dark Bronze, Wall Mount	30	120-277	50,000	7H×7V	3000	5000K	70	7.08 X 4.42 X 1.61	1
3665114	SSL-SFL1/45W/50/UNV/DB/KNC	45W, 50K, 120-277V, Dark Bronze, Knuckle	45	120-277	50,000	7H×7V	5400	5000K	70	8.26 X 5.16 X 2.45	1

Applications

Building facades, displays, landscaping, security lighting, walkways and other work areas.

Mounting Options

Trunnion Mount



Wall Mount (30W & 45W ONLY) 4 & 5" J-box mounting



Ordering Information Example: SSL-SFL1/15W/50/UNV/DB/KNC

Family Name	Fixture Type	Wattage	CCT	Voltage (V)	Body Finish	Mounting
SSL (Solid State Lighting)	SFL1 (Slim Flood)	15W 30W 45W	50 (5000K)	UNV (120~277V)	DB (Dark Bronze)	KNC (Knuckle) WM (Wall Mount) TR (Trunnion)