


LED FIXTURE

RIGID Series

LED Slim Panel PRO-SP

Slim design allows it to be installed in low plenum ceilings.



Features & Benefits

- Type IC Rated – approved for direct contact with insulation, FT4 rated cable
- Isolated internal driver in junction box – fast and easy to install
- Finish Color White, 4", damp location rated
- PC lens aluminium body

Energy Star approved

L70 @ 50,000 Hrs

Dimmable Triac down to 10%

High CRI (80+)

Warranty


5-year limited warranty in commercial use from the date of purchase

Operating temperature range between -20°C and +40°C

Applications

Residential / Commercial, Schools, Retirement Homes, University, Supermarkets, Shops, Hotels, Conference Rooms, Office Lighting, Show Room, Corridor, Kitchens etc.

Dimensional drawing



M.O.D	Cut-Out	H
5 3/8"	4 1/4"	1 1/4"

Ordering Information Example: PRO-SP/4/9.5W/30/120/WH/D

Family Name	Fixture Type	Size	Wattage	CCT (Kelvin)	Voltage	Finish Color	Dimmable
PRO	SP (Slim Panel)	4 (4")	9.5W	30 (3000K) 40 (4000K)	120 (120V)	WH (White)	TRIAC

Product Specification

Ordering Code	Energy Star	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Case QTY.
3662133	Yes	PRO-SP/4/9.5W/30/120/WH/D	9.5W	120V	50,000	600	3000	>80	6
3662136	Yes	PRO-SP/4/9.5W/40/120/WH/D	9.5W	120V	50,000	600	4000	>80	6