

# LED FIXTURE

## SSL Series



Photo shown with installed sensor



## LED Compact Parking Garage Canopy SSL-CPG

120-347V Auto-Sensing Driver  
1-10V dimming  
Multiple Kelvin (CCT) Selection

### Features & Benefits

cULus listed	Suitable for J-BOX mounting, and pendant mounting
System light efficacy $\geq 135$ lm / W	CRI $\geq 80$ , L70@ 50,000 Hrs
Switchable CCT (30K/40K/50K)	Voltage 120-347V Auto-Sensing
White finish	150° Beam spread, PC Lens
1-10V DC dimming option	Installed sensor socket allows for ease of sensor installation, sensor sold separately
IP 65 rated, wet location	

### Warranty

5-year limited warranty in commercial use from the date of purchase  
Operating temperature range between -40°C and +50°C

### Applications

Parking structures, storage areas, shopping area walkways, entryway, and low level security

### Ordering Information Example: SSL-CPG/25W/MK/120-347V/WH/D


Family Name	Fixture Type	Wattage	CCT (Kelvin)	Voltage	Finish	Dimmable	Options
SSL (Solid State Lighting)	CPG (Compact Parking Garage Canopy)	25W, 40W 60W, 75W 100W	MK (Multi CCT)	120-347V	WH (White)	D (Dimmable)	SSL-CPG/LV/12V/SENSOR SSL-CPG/LV/12V/CONTROLLER

### Product Specification

Ordering Code	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Wet Location	Dimension DxH(inch)	Case QTY.
3664309	SSL-CPG/25W/MK/120-347V/WH/D	25	120-347V	50,000	3500	30-40-50	$\geq 80$	Yes	10 x 3.1	1
3665314	SSL-CPG/40W/MK/120-347V/WH/D	40	120-347V	50,000	5400	30-40-50	$\geq 80$	Yes	10 x 3.1	1
3666315	SSL-CPG/60W/MK/120-347V/WH/D	60	120-347V	50,000	8100	30-40-50	$\geq 80$	Yes	10 x 3.1	1
3666316	SSL-CPG/75W/MK/120-347V/WH/D	75	120-347V	50,000	10100	30-40-50	$\geq 80$	Yes	11 x 3.1	1
3666317	SSL-CPG/100W/MK/120-347V/WH/D	100	120-347V	50,000	13500	30-40-50	$\geq 80$	Yes	11 x 3.1	1
3660154	SSL-CPG/LV/12V/SENSOR	SSL CPG Canopy 12V DC Microwave Sensor								
3660155	SSL-CPG/LV/12V/CONTROLLER	SSL CPG Canopy 12V DC Microwave Sensor Remote Control								

### Dimensional drawing

	DIA/ D	H
25W, 40W, 60W	10"	3.1"
75W, 100W	11"	3.1"



SSL-CPG/LV/12V/SENSOR



SSL-CPG/LV/12V/CONTROLLER