


# LED LAMP

ARTISAN Series



## LED T6, T9, T10, T14

Low Flicker LOW non visible FLICKER



15,000hrs: 2-year; 25,000hrs: 3-year limited warranty

Operating temperature range -20 °C ~ +40 °C



### Features & Benefits

- Reduced flicker down to 10%
  - Compare to 6.6% traditional incandescent
  - Far below California T20 standard 30%
  - Significantly improve light quality
  - Optimize eye comfort

With clear, amber glass cover


25,000 hour life (L70)\*, high CRI (80+), dimmable,

Beam angle 330°\*

Damp location rated

\* For applicable models, see product specification below

### Dimensional Drawing



### Ordering Information Example: AR-T6LF/5W/30/E12/D/C

Family Name	Lamp Type	Wattage	CCT	Base	Dimmable	Cover
AR (Artisan)	T6LF (T6, Low flicker)	4W	22 (2200K)	E12	D (Dimmable)	C (Clear) A (Amber)
	T9LF (T9, Low flicker)	5W	27 (2700K)	Blank (E26)		
	T14LF (T14, Low flicker)	8W	30 (3000K)			
	T10 (T10, Long neck)					

### Product Specification

Ordering Code	Model Number	Watts	Replacement Filament	Replacement Incandescent	Base	Voltage (V)	Hour Rating	Beam Angle*	Initial Lumens(lm)	CCT(K)	CRI	Damp Location	M.O.L. (inch)	Case QTY.
1771219	AR-T6LF/5W/30/E12/D/C	5	-	50W	E12	120	15,000	330	500	3000	80	Y	3.84	50
1771140	AR-T9LF/4W/27/D/C	4	-	40W	E26	120	15,000	330	350	2700	80	Y	5.71	50
1771206	AR-T9LF/4W/30/D/C	4	-	40W	E26	120	15,000	330	350	3000	80	Y	5.71	50
1771928	AR-T9LF/4W/22/D/A	4	45W	-	E26	120	15,000	330	300	2200	80	Y	5.71	50
1771207	AR-T14LF/5W/30/D/C	5	-	60W	E26	120	15,000	330	500	3000	80	Y	4.17	50
1772204	AR-T10/8W/30/D/C/L**	8	-	80W	E26	120	20,000	330	750	3000	80	Y	11.9	100

\*\* AR-T10 is not the low flicker item