

LED Slim Panel

SEL-SP/FR	Segment	Wattage Range	Lumen Range
Commercial & Residential	12W-15W	800-1100lm	



Ordering Information Example: SEL-SP/FR/4/12W/MK5/120V/WH/D

Family Name	Fixture Type	Size	Wattage	CCT	Voltage	Finish	Dimmable
SEL (SELECT)	SP/FR (Slim Panel, Fire Rated)	4 (4") 6 (6")	12W 15W	MK (Selectable CCT)	120V	WH (White)	D (Dimmable)

Product Specification

Ordering Code	Energy Star	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating	Initial Lumens (lumen)	CCT (K)	CRI	Beam Angle	Wet Location	Dimension D×H (inch)	Case QTY.
3665320	Yes	SEL-SP/FR/4/12W/MK5/120V/WH/D	12	120	50,000	800	27-30-35-40-50	≥90	120°	Yes	5" × 1.3"	18
3665321	Yes	SEL-SP/FR/6/15W/MK5/120V/WH/D	15	120	50,000	1100	27-30-35-40-50	≥90	120°	Yes	7" × 1.3"	18
3660443	-	SP/FR/4/Trim/BK	Select Slim Panel 4", Black Trim									
3660444	-	SP/FR/6/Trim/BK	Select Slim Panel 6", Black Trim									

!!

All our fire-rated downlight products have been rigorously tested to meet safety and performance standards by independent, accredited laboratories. Please note that testing methodologies may vary slightly between laboratories, and compliance requirements can differ depending on local building codes and regulations.

We encourage our clients to review the testing reports available for our products and consult with relevant authorities or professionals to determine their suitability for specific applications or jurisdictions. The final decision regarding compliance with building codes rests with the client.

For access to our testing reports or further assistance, please contact your sales rep.

Accessories

SP/FR/Trim/BK



Related Products



RGD-CDR



RGD-CHY2



RGD-JH



RGD-HS