

LED Slim Panel



SEL-SP/FR	Segment	Wattage Range	Lumen Range
	Commercial & Residential	12W-15W	800-1100lm

Features

- 2-hour fire rating secured by a reinforced and heat-resistant steel backplate design.
- Edge-lit slim profile suitable for low-depth installation.
- Certified airtight, FT6 cable.
- 5 field selectable CCT options (27K, 30K, 35K, 40K & 50K) with CRI 90.
- Wet location rated for a wide variety of applications.
- IC-rated for direct contact with insulation.

Specifications

Housing:

Pressure die-cast aluminum body with a steel backplate for reinforced heat resistance.

Optics:

Premium-grade opal diffuser for even and glare-free light distribution.

Mounting:

Recessed mounting with spring clamps.

Driver:

Commercial-grade 120V driver with an operating temperature range of -20°C to +40°C.


LED:

5 field selectable CCT options of 27K, 30K, 35K, 40K & 50K.

Controls:

Compatible with most mainstream TRIAC dimmers.


Dimensional Drawing



	D	Cut-out	H
SEL-SP/FR/4 (4")	5"	4.25"	1.3"
SEL-SP/FR/6 (6")	7"	6.25"	1.3"



Polar Candela



Applications



Offices



Malls



Hotels



Residences

LED Slim Panel



SEL-SP/FR	Segment	Wattage Range	Lumen Range
	Commercial & Residential	12W-15W	800-1100lm

Ordering Information Example: SEL-SP/FR/4/12W/MK5/120V/WH/D

Family Name	Fixture Type	Size	Wattage	CCT	Voltage	Finish	Dimmable
SEL (SELECT)	SP/FR (Slim Panel, Fire Rated)	4 (4") 6 (6")	12W 15W	MK (Selectable CCT)	120V	WH (White)	D (Dimmable)

Product Specification

Ordering Code	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating	Initial Lumens (lumen)	CCT (K)	CRI	Beam Angle	Wet Location	Dimension D×H (inch)	Case QTY.
3665320	SEL-SP/FR/4/12W/MK5/120V/WH/D	12	120	50,000	800	27-30-35-40-50	≥90	120°	Yes	5" × 1.3"	18
3665321	SEL-SP/FR/6/15W/MK5/120V/WH/D	15	120	50,000	1100	27-30-35-40-50	≥90	120°	Yes	7" × 1.3"	18

Related Products



RGD-CDR



RGD-CHY2



RGD-JH



RGD-HS