

LED FIXTURE

PRO Series



LED Strip Light PRO-EC2

Linear LED strip light, 120-347V auto-sensing driver with 0-10V dimming
Selectable Kelvin (CCT) & Selectable Wattage



5-year limited warranty

Operating temperature range -20 °C ~ +50 °C



Features & Benefits

- cETLus and DLC listed
- Selectable Kelvin (CCT) & Selectable Wattage
- 120-347V Auto-sensing driver, 0-10V dimming
- L70 @ 50,000 Hrs, CRI ≥80
- White metal finish, polymer diffusing lens
- Wall and surface mounting
- Damp location rated

Dimensional Drawing



	L	W	H
4FM	47.67"	2.4"	2.3"
8FM	95.28"	2.4"	2.3"

Ordering Information Example: PRO-EC2/4FM/MW/MK/120-347V/D

Family Name	Fixture Type	Size	Wattage	CCT	Voltage	Dimmable	Option
PRO	EC2 (LED Eco-Commercial)	4FM (4') 8FM, 8FL (8')	MW (Selectable Wattage)	MK (Selectable CCT)	120-347V	D (0-10V dimming)	A/LV6SA (Low voltage sensor) EM (Emergency BU)

Product Specification

Ordering Code	DLC	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating (L70)	Beam Angle	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Damp Location	M.O.L (inch)	Case QTY.
3680353	Yes	PRO-EC2/4FM/MW/MK/120-347V/D	40-35-30	120-347V	50,000	120°	5420-4970-4260	35-40-50	>80	Yes	47.67	6
3682269	Yes	PRO-EC2/8FM/MW/MK/120-347V/D	80-70-60	120-347V	50,000	120°	10400-9150-7800	35-40-50	>80	Yes	95.28	4
3682297	Yes	PRO-EC2/8FL/MW/MK/120-347V/D	100-90-80-70-60	120-347V	50,000	120°	15500-13500-12000-10500-9000	30-35-40-50-65	>80	Yes	95.28	4
3660214	-	PRO-EC/MTG/H-C/KIT	Hook and chain mounting kit, includes, 2x "S" hooks and 2 x 1.05m length of link chain and 2 x hooked wood screws									

DLC Certification

Ordering #	Full Model Number	Primary Use	DLC Standard	DLC Premium
3680353	PRO-EC2/4FM/MW/MK/120-347V/D	Direct Linear Ambient Luminaires	S-H1K476	-
3682297	PRO-EC2/8FL/MW/MK/120-347V/D	Direct Linear Ambient Luminaires	S-642CSQ	-
3682297	PRO-EC2/8FL/MW/MK/120-347V/D	High-Bay Luminaires for Commercial and Industrial Buildings	S-Y229P6	-
3682269	PRO-EC2/8FM/MW/MK/120-347V/D	Direct Linear Ambient Luminaires	S-SMG4VY	-
3682269	PRO-EC2/8FM/MW/MK/120-347V/D	High-Bay Luminaires for Commercial and Industrial Buildings	S-9DYCD6	-



PRO-EC/MTG/H-C/KIT