


PAR LED Lamps

HD-PAR/I90/5CCT



3-year limited warranty

Operating temperature range -40 °C ~ +40 °C



Features & Benefits

cETLus listed

5CCT Selectable (27/30/35/40/50K)


High CRI (90+), Dimmable

Glass lens with perfect light distribution

25,000 hrs average life

Wet location rated

Dimensional Drawing



Ordering Information Example: HD-PAR30LN/I90/12W/5CCT/WFL40/D/BK

Family Name	Lamp Type	CRI	Wattage	CCT	Beam Angle	Dimmable	Finish
HD	PAR20 PAR30LN (PAR30 Long neck) PAR38	I90 (CRI 90+)	7W 12W 16W	5CCT (5CCT Selectable)	WFL40 (40°)	D (Dimmable)	BK (Black) Blank (White)

Product Specification

Ordering Code	Model Number	Wattage (W)	Base	Voltage (V)	Hour Rating	Beam Angle	CCT(K) Lumens(lm)	CRI	Enclosed Fixture Application	Wet Location	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
1783001	HD-PAR38/I90/16W/5CCT/WFL40/D	16	E26	120	25,000	40°	27/30/35/40/50 1457/1488/1502/1500/1469	90	No	Yes	4.8	5.31	20
1783003	HD-PAR38/I90/16W/5CCT/WFL40/D/BK	16	E26	120	25,000	40°	27/30/35/40/50 1457/1488/1502/1500/1469	90	No	Yes	4.8	5.31	20
1782004	HD-PAR30LN/I90/12W/5CCT/WFL40/D	12	E26	120	25,000	40°	27/30/35/40/50 852/970/887/868/857	90	No	Yes	3.74	4.84	30
1782006	HD-PAR30LN/I90/12W/5CCT/WFL40/D/BK	12	E26	120	25,000	40°	27/30/35/40/50 852/970/887/868/857	90	No	Yes	3.74	4.84	30
1781001	HD-PAR20/I90/7W/5CCT/WFL40/D	7	E26	120	25,000	40°	27/30/35/40/50 520/553/567/548/531	90	No	Yes	2.47	3.46	50
1781003	HD-PAR20/I90/7W/5CCT/WFL40/D/BK	7	E26	120	25,000	40°	27/30/35/40/50 520/553/567/548/531	90	No	Yes	2.47	3.46	50