LED FIXTURE

PRO Series



Linear 4' LED strip light, 120-347V auto-sensing driver with 0-10V dimming Selectable Kelvin (CCT) & Selectable Wattage



5-year limited warranty

Operating temperature range -20°C ~ +50°C



Features & Benefits

Teatures & Denents	Dimensional Drawing						
cULus listed		1					
Selectable Kelvin (CCT) & Selectable Wattage, 4' length						-	I
120-347V Auto-sensing driver, 0-10V dimming			:	•		* • . I	W
L70@50,000Hrs, CRI≥80							
White metal finish, polymer diffusing lens				L	W	н	
Wall and surface mounting			4FT	47.64″	2.44″	3.03″	
Damp location rated							

Dimensional Drawing

Ordering Information Example: PRO-EC2/4FM/MW/MK/120-347V/D

Family Name	Fixture Type	Size	Wattage	сст	Voltage	Dimmable
PRO	EC2 (LED Eco-Commercial)	4FM (4')	MW (Selectable Wattage)	MK (Selectable CCT)	120 -347V	D (0-10V dimming)

Product Specification

Ordering Code	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating (L70)	Beam Angle	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Damp Location	M.O.L (inch)	Case QTY.
3680353	PRO-EC2/4FM/MW/MK/120-347V/D	40-35-30	120-347V	50,000	120°	5420-4970-4260	35-40-50	>80	Yes	48	6
3660214	PRO-EC/MTG/H-C/KIT	Hook and chai	n mounting kit, includ	des, 2 x "S" hooks and	2 x 1.05m leng	th of link chain and 2 x hooked wo	ood screws				



PRO-EC/MTG/H-C/KIT





