

MR16 LED Light Bulbs

VIV-MR16/X25



3-year limited warranty


Operating temperature range -20° C ~ +45° C



Features & Benefits

cUL listed
High CRI (80+), dimmable
Enclosed fixture application
Short Neck
25,000 hrs average life
Damp location rated

Dimensional Drawing



Ordering Information Example: VIV-MR16/X25/7W/30/WFL45/JDR/S/D

Family Name	Lamp Type	Wattage	CCT(K)	Beam Angle	Base	Neck Length	Dimmable
VIV (Vivid)	MR16/X25	7W	27 (2700K) 30 (3000K) 40 (4000K)	WFL45 (45°)	JDR (E26)	S (Short)	D (dimmable)

Product Specification

Ordering Code	Model Number	Wattage (W)	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture	Damp Location	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
1752257	VIV-MR16/X25/7W/27/WFL45/JDR/S/D	7W	E26	120	25,000	45°	560	2700	80	Yes	Yes	1.97	2.07	100
1752246	VIV-MR16/X25/7W/30/WFL45/JDR/S/D	7W	E26	120	25,000	45°	560	3000	80	Yes	Yes	1.97	2.07	100
1752442	VIV-MR16/X25/7W/40/WFL45/JDR/S/D	7W	E26	120	25,000	45°	560	4000	80	Yes	Yes	1.97	2.07	100